



# THREE PHASE EPS BOX PRO



Max. input current  
(per phase) 63A



Safety



IP65 Rated



Quickly Installation

- Max. input current (per phase) 63A
- PC+ABS ,Robust plastic enclosure IP65
- Easy installation, plug and play
- Applied to residential, commercial solar installations
- Compatible with H3/AIO H3 series
- Automatically switch to Off-Grid state



## SPECIFICATIONS

<b>Model</b>	EPS BOX PRO
--------------	-------------

### UTILITY SUPPLY

Rated Voltage	220 / 380VAC, 230 / 400VAC, 3L / N / PE
Rated Frequency	50 / 60Hz
Max. Input Current (Per Phase)	63A

### INVERTER GRID

Rated Voltage	220 / 380VAC, 230 / 400VAC, 3L / N / PE
Rated Frequency	50 / 60Hz
Max. Input Current (Per Phase)	25A

### INVERTER EPS

Rated Voltage	220 / 380VAC, 230 / 400VAC, 3L / N / PE
Rated Frequency	50 / 60Hz
Max. Input Current (Per Phase)	25A

### Load

Rated Voltage	220 / 380VAC, 230 / 400VAC, 3L / N / PE
Rated Frequency	50 / 60Hz
Max. Output Current	63A

### Communication Interface

RS-485 (Meter)	
----------------	--

### General Data

Cooling Concept	Natural
Installation	Wall-mounted
Operating Temperature Range (°C)	-25 ~ +60 (derating at 45)
Dimensions (W * H * D) (mm)	550 * 420 * 140
Dimensions of packing (W * H * D) (mm)	660 * 530 * 245
Net Weight (kg)	9.3
Gross Weight (kg)	11
Ingress Protection	IP65

