



21	7-216249A157S	Cap 2	1	Brass		
20	7-304086A506E7	Gasket	1	EPDM		
19	7-305001A501C7	Chain	1	Silicon Rubber		
18	7-502401A235N	Screw	1	Steel		
17	7-407006A212L3-N	Handle	1	Aluminium		
16	7-216384A157S-5000	Body Cap	1	Brass		
15	7-202019A157CP	Ball	1	Brass		
14	7-302128F506D7	O-ring-1	2	EPDM		
13	7-2030005A157S	Stem	1	Brass		
12	7-301014A412Y8	Seats	2	PTFE		
11	126710S704-056-5000	Lead seal	1	Lead		
10	126710S704-055-5000	Seal wire	1	Steel		
9	126710S704-018-5000	Cap	1	POM		
8	126710S704-017-5000	Clips	1	Steel		
7	009-15X2EPDM	O-ring(1)	1	EPDM		
6	126710S704A-042-5000	The valve core	1	Brass		
5	7-306095A412Y8	Gaskets 2	1	PTFE		
4	126710S704-015-5000	Swivel Nut	1	Brass		
3	126710S704A-014-5000	Connector	1	Brass		
2	126710S704-007-5000	Gaskets 1	1	AFM34		
1	126710S704A-001-5000	Body	1	Brass		

- NOTE:
1. Operating temperature range: 0° C~120° C.
 2. Operating pressure: max. 10 bar.
 3. Threads: DIN ISO 228/1.
 4. Production date: XX(week) YY (Year) Adjustable

This drawing must not be communicated to third parties, not copied, nor abused in any other way.

Modification

NO.	Changes	Name	Date

NO.	Changes	Name	Date

Specification